



### Audio

**Frequency response** 35Hz – 22kHz

**Drivers** 2 x 75mm custom full-range polypropylene cone neodymium satellite drivers, 130mm subwoofer

**Amplifier** 90W Class AB

**Enhancements** Bass, treble, sub level, loudness, 3D audio

**Digital to analogue** Burr-Brown 32-bit 192kHz DAC

**Analogue to digital** 24-bit 192kHz ADC

### Connectivity

**Multi-room** Synchronised audio on up to 5 devices

**Radio** DAB / DAB+ / FM with RDS (87.5-108MHz) and Internet Radio

**Bluetooth** V4.0, SBC, AAC, A2DP, aptX, aptX HD

**Wi-Fi** 802.11b/g/n; WEP, WPA & WPA2 security

**Ethernet** RJ45

**Music services** Spotify Connect, Amazon Music, Deezer, Tidal

**Media** Compatible with UPnP™ DLNA media servers; MP3 up to 48kHz 320kbps, AAC up to 96kHz 320kbps, FLAC\* up to 24-bit 48kHz, WAV up to 16-bit 48kHz or 24-bit 44.1kHz, WMA up to 44.1kHz 320kbps

\* FLAC files not supported in Multi-room mode

**CD player** CD, CD-ROM, CD-R/RW discs; MP3, WMA & AAC up to 320kbps

**Line-in** Stereo RCA (max 2.3Vrms)

**MM phono input** Stereo RCA input with integrated RIAA phono stage (up to 8mV)

**Digital input** 24-bit 192kHz optical TOSLINK

**Line-out** Line-level stereo RCA (2.0Vrms)

**Headphone** 3.5mm jack, 25mW into 16-32 Ohm

**USB** Fat32 memory stick playback, 5V 1A (5W)

**Aerial** Removable telescopic

**Aerial connector** 75Ω F-type connector

### Features

**Remote control** wireless

**App control** UNDOK (iOS & Android)

**Display** High-contrast OLED

**Alarms** 2 (daily, once, weekends, weekdays)

**Auto standby** Automatic low power mode

**Adjustable input levels** Line, optical, phono

**System languages** English, French, German, Spanish

### General Specifications

**Finishes** Rich walnut or soft grey with grey fabric grille. Signature Edition in piano black lacquer with anthracite fabric grille. MiE in smoked grey veneer and wooden slatted grille.

**Remote battery** CR2032

**Box contains** R5 High Fidelity Music System, 2m mains power cable, remote control, remote control battery, telescopic aerial, aerial spanner, user guide

**Power supply** Linear 120W amplifier power supply and 25W switch mode logic power supply

**Power input** 100-120/200-240VAC, 50-60Hz,

250V T3.15A fuse, 2m power cable with 5A fuse fitted

**Power consumption** 2W standby, 13W nominal

**Product dimensions** H142 × W520 × D300mm

**Product weight** 10.0kg

**Inner carton dimensions** H395 × W615 × D230mm

**Packaged weight** 12.3kg

**Shipping carton dimensions** H420 × L625 × W245mm

**Shipping carton weight** 0.9kg

**Gross weight** 13.2kg (1 unit)

**Rich Walnut product code/EAN**

R5-WAL-U / 5060637250020

**Soft Grey product code/EAN**

R5-SG-U / 5060637250037

**Signature Edition product code/EAN**

R5-SE / 5060637250099

**Made in England product code/EAN**

R5-MiE / 5060637250136